



SPORT CRUISER

PRINCIPAL CHARACTERISTICS

L.O.A	11.99 m	J=	4.85 m
L.W.L	11.90 m	I=	14.60 m
Beam	6.42 m	E=	5.60 m
Draft (Low aspect Keels)	1.2m	P=	14.50 m
Displacement (L.S)	5000 kg		
Load carrying cap	4000 kg	Mainsail	57.20 sq m
Auxiliaries	2 x 21 hp	100% Fore-triangle	31.60 sq m
Height of DWL	17.82 m	Storm jib	6.00 sq m

HULL, DECK & BULKHEADS

Using only the highest grade Lloyds approved materials.

- Polyester resin and multi axial stitched E-glass fabrics
- Core sandwich, vacuum bonded construction
- Steering Consol with instrument panel, engine controls, winch pads, steering pedestal and locker.
- Reinforcing built-in for all deck fittings and high load areas.
- Bulkheads are bonded in place.
- Forward water-tight compartments.
- Low aspect keels
- Rudders are fixed.
- Mast beam and aft cross-beam with lockers
- Anti-fouling over epoxy osmosis barrier
- Custom companionway ladders

EXTERIOR MODULES

- Custom Pod with table & seating

INTERIOR MODULES

All interior modules have solid Teak wood trimming and the floor boards have Holly & Teak finish.

Aft Cabins

- Two queen-sized double bunks with mattresses
- Storage cabinet & overhead locker
- SS Rod hangers under upper cabinet

Galley

- Stove & sink counter with storage lockers. SMEV Burner X 2 + Sink
- Companionway staircase with balustrade & grab-rail.
- Overhead storage locker 300mm deep plus full length

Navigation Centre

- Chart table with cabinet and overhead switchboard
- Companionway staircase with grab-rails

Head Compartments

- Washbasins with locker. Includes Vanity Cabinets and SS rod hanger on ceilings

Forward Cabins

- Two single bunks with internal lockers
- GRP ladder

DECK HARDWARE

Hatches & Portlights

- 4 x size 60 medium profile Lewmar hatches
- 2 x size 70 medium profile Lewmar hatches
- 8 x size 30 Atlantic Lewmar Portlights

Winches

- 2 x 44CST winches (main sheet)
- 2 x 46CST sheet winches on Pedestal
- 2 x power-grip lock-in winch handles & pockets

Jammers

- 1 x single XCS/1 single rope clutch – main halyard
- 2 x single XCS/1 single rope clutch – Genoa sheets
- 2 x single XCS/1 single rope clutch – Genoa halyards

Mainsheet System

- 2 x 90 mm Spring loaded Blocks
- 2 x 90mm single block on boom aft end
- 2 x 90mm Horizontal Blocks
- 2 x single XCS-1 Jammers

Genoa System

- 1 x Lewmar 2916 2410 Track 3 M
- 1 x Lewmar 2903 2100 Car
- 2 x Lewmar 2917 2039 Simple Track
- 2 x Sparcraft custom Blocks
- 2 x single XCS-1 Jammers

General Blocks & Hardware

- 2 x size 3 snatch blocks - reefing lines
- 10 x 250mm mooring cleats
- 6 x S/S stanchions
- 8 x Pad-eyes for Safety Lines
- 6 x pop up pad-eyes

Navigation Lights

- 1 x stern light (LED)
- 1 x port light (LED)
- 1 x starboard light (LED)

Interior Lights

- 2 x dome lights in pod
- 10x fluorescent lights
- 3 x Interior Spot lights

Sailing Instrumentation

- 1 x Tridata
- 1 x VHF
- 1 x Olympic 135 compass, zone B
- 1 x CD player
- 2 x waterproof speakers

Plumbing

- 2 x manual thru deck bilge pumps
- 2 x 1.5" skin fittings
- 4 x remotely mounted bilge pumps
- 4 x float switches
- 4 x horizontal strum boxes
- 4 x skin fittings
- 1 x 12v washdown pump
- 3 x single taps
- 1 x 300L water tank
- 1 x toilet 12v electric
- 1 x 12v hand shower mounted on deck
- 1 x 12v hand shower in starboard head

Anchors & Mooring

- 1 x 20kg delta anchor
- 10m x 10mm anchor chain
- 2 x 10mm galv. D shackles
- 50m x 16mm anchor warp
- 1 x 35lb CQR anchor
- 5m x 10mm anchor chain
- 40m x 16mm moorings warps
- 5 x DH5 fenders 250 x 800mm
- 7.5 x fender lanyards 1.5M x 5 x 10mm
- Bridle & shackles & bull-ring

RIGGING

Mast

- Custom single spreader NG86 mast section (248 x 175)
- Deck stepped untapered
- Anodized natural
- Brackets for navigation lights, windex and wind instruments
- Mast head welded in position, facility for 4 halyards incl 2:1 main & screecher
- Forestay attachment point provided
- Cap tangs complete
- Spinnaker halyard sheave box with deflector
- Sheave box fitted for Genoa halyard
- One set of swept aerofoil spreaders fitted
- Shroud terminals fitted for diamonds
- Sail track for 22mm slides
- Four exit slots of the open skid type
- Fixed gooseneck suitable for slab reefing
- Two luff pennant pad-eyes fitted
- 1 Winch pad to starboard (Main Hal / reef)
- Main boom topping lift facility on mast
- Mast heel
- Mast step
- Mount windex, VHF and tri-colour LED
- Small Windlass holder step in front of Mast

Forward cross beam

- Aluminium section, $\frac{3}{4}$ ton (175 x 115) with mounting flanges
- Natural anodized
- Seagull striker fitted
- Attachment facilities for spinnaker blocks
- 8mm bolt rope track to attach trampoline
- anchor bridal attachments incorporated on both sides of cross beam hull mounts
- 8mm 1 x 19 striker stay including rigging screw
- 2 x welded cleats
- cross beam brackets

Compression Post

- 100mm diameter tube complete with tracks for trampoline
- anodized natural
- attachment point to fit cross-beam
- 50 mm schedule 80 tubing for Anchor

Additional Items

- 2 x anchor rollers on individual bases

Lights

- Tri-Anchor light LED
- Spreader lights
- Steaming light with s/s protector
- Two conduits fitted and wiring to exit grommet at base of mast

Main Boom

- Aluminium section W30 (165 x 101)
- Anodized natural
- Fitting to suit mast gooseneck
- 2 x Mainsheet fairleads fitted
- Attachment points for main sheet
- Three sheave box fitted at aft end of boom to facilitate outhaul and two reefing lines
- Three sheave box forward for reef-lines and outhaul complete with jammers
- Clew strop c/w shackle supplied
- 2 x Attachment points for boom vang

Reef-lines

- Two colour coded 12mm Southern braid reef-lines
- 12mm Southern braid outhaul
- 10mm spectra luff strops with snap shackles

Standard Rigging

- All wire to be Dyform unless otherwise stated
 - forestay 8mm
 - caps 10mm
 - outer diamond 7mm
 - aft intermediates 8mm
- Leather chafe protection where necessary
- UV resistant anti-chafe tapes over the cap shrouds
- Terminals hydraulically swaged
- Rigging screws inclusive

Halyards

- 1 x Main 2:1 10mm braid with custom 2:1 Sparcraft headboard block
- 1 x Genoa 12mm braid complete with captive 'D' shackle
- 1 x Spinnaker 10mm braid line complete with Gibb snap shackle
- 1 x Screecher 10mm braid line complete with Gibb snap shackle

Lazyjacks

- complete with necessary cordage, cleats and attachments
- cordage led internally then via fairleads in spreaders
- stackpack saddles on mast

SAILS:**Full Batten Main**

- Area 57.2 sqm. Crosscut Dacron cloth 10.3oz complete with cover

Jib with hanks & battens

- Area 31, 6 sqm. Crosscut Dacron cloth 8,3oz

Storm Jib

- Area 6 sqm. Radial Dacron cloth 10.18oz_

STEERING SYSYTEM

- 1 x Brake spinner Commodore
- 1 x Quick release Commodore nut
- 1 x Quick mount 13T bulkhead steerer
- 2 x Single articulated sheave 6"
- 2 x Double flat sheave 6"
- 1 x Custom carbon 36" Wheel
- 1 x 1M S/S roller chain 5/8"P
- 6mm S/S wire, swage ends and clamps
- 2 x PX801 AHFT 10 rose joint 5/8" UNF
- Custom Spinlock shaft with fittings for Auto-helm plus mounting bracket

STAINLESS STEEL

- 2 x Chain plates
- 2 x Push pit
- 2 x Gateways
- 2 x Pulpit
- 2 x Rudder stock
- Swim ladder on inside of transom
- 8 x Grab rails

ELECTRICS

- Switch panel with ammeter and volt meter
- Circuit breakers and switches
- 2 x engine start batteries
- 4 x Load batteries
- 2 x 75 Watt solar panels
- Cabling and conduit
- Battery switches
- 110 volt shore power plug
- Link 1000 voltage regulator system
- Alternator/ temperature display at Helm
- 2 x 12 Volt outlets
- 4 x Bilge alarms at helm

ENGINES

- 2 x 21Hp YANMAR 3YM20C Inboards X SD20-1 sail drive leg

SAFETY EQUIPMENT and Life-Raft / Dinghy

- Owner to supply (SAMSA, USCG or CE approved)

ESTIMATED PRICING: DEPENDENT ON FINAL SPECIFICATIONS

This is a guide line price only; we can still customise the interior and deck layout according to your requirements. **See attached Price List with Optional Extras**

Note: Due to ongoing development & availability of all listed items, Scape Yachts reserves the right to change or modify any specifications or standard equipment.

Our standard conditions of sale apply. NB: Prices quoted are ex factory and in accordance with our standard Agreement of Sale. Zero VAT if sold to outside of South Africa.